



MedeA CED

Compute Key Thermodynamic Characteristics of Molecular Systems

At-a-Glance

The CED module automates calculation of the cohesive energy density of molecular systems, together with the closely related solubility parameter, and heat of vaporization. Both quantities have been widely used in expressions predicting a variety of material properties, including tensile and bulk moduli, surface tension, glass temperatures, stress to initiate crazing, and thermodynamic compatibility of mixtures and blends, to cite a few examples⁵.

Key Benefits

- Performs *on-the-fly* computation of CED, avoiding the need to save large trajectory files
- Reports van der Waals and electrostatic components separately
- Reports related quantities such as the heat of vaporization of fluids conveniently
- Works with JobServer and TaskServer to run your calculations on the appropriate hardware, centralizing the results
- Integrates with MedeA Forcefields for advanced forcefield handling and assignment of a wide variety of organic liquids and amorphous materials

The term **cohesive energy density** (cohesive energy per unit volume, or CED), was introduced by physical chemist George Scatchard in his 1931 theoretical treatment of the thermodynamics of mixing of non-electrolyte solutions², which was the result of studies initiated more than a decade earlier by solution theory pioneer Joel Hildebrand. Here, the term “cohesive energy” represents the increase in energy of a compound if all the intermolecular forces are removed - e.g. as would occur if all molecules were to be separated by an in-

finite distance. Scatchard's theory predicted that the enthalpy of mixing of a binary non-electrolyte mixture would be found by the product of the volume fractions of the components, multiplied by a term involving the differences in the square roots of the cohesive energy densities of the components. Hildebrand subsequently designated the latter as the solubility parameters (δ_i) of the individual pure components³.

Identification of the cohesive energy with the energy required to separate molecules in a liquid by an infinite distance provides a convenient method for experimental determination of cohesive energy densities and solubility parameters from measured enthalpies of vaporization, namely using the relation:

$$CED = \left(\frac{\rho}{M}\right)(\Delta H_v - RT)$$

where ρ and M denote the density and molar mass, R is the gas constant, and T the temperature.

‘The MedeA CED module makes it really straightforward to include this important property calculation in any simulation workflow. It automatically performs the essential averaging over configurations without having to save large unwieldy trajectory snapshots, and delivers the results in a format easily imported into database and spreadsheet applications.’

In classical forcefield-based molecular simulations, the cohesive energy essentially corresponds to the intermolecular nonbond energy averaged over an equilibrium statistical mechanical ensemble of liquid configurations. Although this is conceptually simple, in practice the computation may

⁵ van Krevelen, D.W., *Properties of Polymers*, 3rd Ed., Elsevier, New York (1990)

² Scatchard, G., *Equilibria in Non-Electrolyte Solutions in Relation to the Vapor Pressures and Densities of the Components*, Chem. Rev., **8**, 321-333 (1931).

³ Hildebrand, J.H., *A Critique of the Theory of Solubility of Non-Electrolytes*, Chem. Rev., **44**, 47-45 (1949).

require the examination of thousands of individual configurations. The *CED* module of the MedeA LAMMPS software is designed to perform this operation automatically without the need for post-processing of snapshots extracted from large and potentially unwieldy trajectory files. Moreover, since the nonbonded energy typically contains contributions from both coulombic and van der Waals repulsive and dispersive interactions, *CED* automatically reports this decomposition, which can be helpful when the solubility parameter approach is used to predict or understand thermodynamic compatibility of different materials⁴. As with other property calculations within the MedeA environment, monitoring convergence and analyzing uncertainties are performed automatically for the CED, and associated quantities are reported at the end of the simulation.

Material	ρ expt. (g/cm ³)	ΔH_{vap} expt. (kJ/mol)	PCFF+		COMPASS	
			$\Delta\rho$ %	$\Delta\Delta H_{\text{vap}}$ %	$\Delta\rho$ %	$\Delta\Delta H_{\text{vap}}$ %
C ₅ H ₁₂	0.6214	26.75	-0.12%	-0.32%	-1.50%	-3.29%
C ₆ H ₁₄	0.6548	31.73	-0.02	-0.13	-1.02	-1.94
C ₇ H ₁₆	0.6795	36.66	0.01	-0.02	-0.73	-0.96
C ₈ H ₁₈	0.6985	41.53	0.03	0.15	-0.60	-0.14
C ₉ H ₂₀	0.7138	46.43	0.09	0.24	-0.50	0.42
C ₁₀ H ₂₂	0.7263	51.39	0.14	0.05	-0.47	0.58
C ₁₁ H ₂₄	0.7366	56.43	0.20	0.15	-0.20	1.29
C ₁₂ H ₂₆	0.7452	61.51	0.33	0.14	-0.13	1.56
C ₁₃ H ₂₈	0.7528	66.43	0.28	0.23	-0.13	1.88
C ₁₄ H ₃₀	0.7593	71.30	0.33	0.49	-0.03	2.36
C ₁₅ H ₃₂	0.7650	76.11	0.29	0.66	0.00	2.84
C ₁₆ H ₃₄	0.7700	81.38	0.32	0.17	0.19	2.89
C ₁₇ H ₃₆	0.7745	86.02	0.43	0.89	0.06	3.23
C ₁₈ H ₃₈	0.7785*	-	0.32	-	0.03	-
C ₁₉ H ₄₀	0.7821*	-	0.41	-	0.04	-
C ₂₀ H ₄₂	0.7853*	-	0.39	-	-0.04	-
Mean Absolute Error			0.23%	0.28%	0.36%	1.80%

the quality of intermolecular potentials, or force-fields. This is shown in the following table, which

⁴ Barton, A.F.M., *CRC Handbook of Solubility Parameters and Other Cohesion Parameters*, 2nd Edition, CRC Press, Boca Raton, Florida, USA (1991).
 The CED and ΔH_{vap} values for a homologous series of hydrocarbons calculated using the Materials Design® PCFF+ forcefield, clearly illustrating the high accuracy achievable using MedeA software.

Computational Characteristics

- Uses the *MedeA LAMMPS* engine for high performance on any computer from a scalar workstation to a massively parallel cluster

Required Modules

- *MedeA Environment*
- *MedeA LAMMPS*

Related Modules

- *MedeA Amorphous Materials Builder**
- *MedeA HT-Launchpad*
- *MedeA HT-Descriptor*

Find Out More

Learn more about how *MedeA CED* can be used to compute one of the most commonly used predictors of the properties of polymers and organic materials by viewing the following webinar:

- [An Introduction to the MedeA user interface](#)

In addition to the use of the CED in correlating and predicting cohesive and adhesive properties of materials, calculation of heats of vaporization (ΔH_{v}) can be particularly useful for assessing